



Standard Features

Construction

- Solid doors with exterior stainless steel front
- Heavy duty hinge with self closing mechanism
- Aluminum interior
- Recessed handle
- Heavy duty epoxy shelves
- Robust body with 2-1/2", thick walls, injected with CFC-free polyurethane
- Solid door, save energy by preventing warm air from reaching your products
- External temperature display and power indicator
- 5" swivel casters
- NSF Certified

Refrigeration

- Forced air evaporator for quick temperature "Pull Down"
- Heavy duty condensing unit with R-404 refrigerant, located in front for easy access maintenance
- 10 year life fan motors

Electrical Requirements

- 115V-60Hz-1ph
- 10' power cord, included

Options

- Heavy duty shelves
- Electric Condensate pan



SAVF-20-T



SAVF-40-T

SAVF-20-T

31.5" D x 23" L x 72.5" H
18 Cubic ft. • 1 Solid Door • 4 Shelves

SAVF-40-T

31.5" D x 46.5" L x 72.5" H
37 Cubic ft. • 2 Solid Door • 8 Shelves

• Specification subject to change without notice.

FOGEL GROUP USA, LLC

831 E Cayuga Street, Philadelphia, PA 19124 USA • (215) 464-6800 • 1-800-344-8222
Fax (215) 969-4890 • E-Mail: sales@fogelusa.com • www.fogelusa.com



Reach In Freezers — Top Mount, Narrow



Technical Data

Model #	SAVF-20-T	SAVF-40-T
Outside Dimensions		
Depth w/Door	31.5"	31.5"
Length	23"	46.5"
Height w/Casters	78.5"	78.5"
Door Size	20.25" x 56.75"	20.25" x 56.75"
Door Type	1 swing	2 swing
Inside Dimensions		
Depth	27.4"	27.4"
Length	18.25"	42"
Height	54.6"	54.6"
Shelf Size	17.75" x 25.75"	20.25" x 23.625"
# of Shelves	4	8
Capacity: Cubic Foot	18	37
Specifications		
Operating Temperature	0°F to 10°F	0°F to 10°F
Refrigerant	R-404A	R-404A
Compressor Size HP	1/3	1/2
Defrost	3@30min	3@30min
Voltage	115	115
Amperage	7.5	12.0
Cord and Plug	yes	yes
Shipping Dimensions		
Depth	33"	33"
Length	26"	48.75"
Height	75.5"	75.5"
Gross Weight lbs.	257	386
Cubic feet	38	70

- Specification subject to change without notice.

